

Characteristics of ALFA D 2564 B

Adhesive:

ALFA D 2564 B is for bonding paper, cardboard, aluminum foil, PVC, PE pretreated, OPP and coatings. Especially for the bonding of the bottom of paper bags.
When gluing of printed papers, the risk of bleeding of colors is minimal.

Application:

Suitable for roller or wheeler with vertical or top Glue Unit.

Properties:

ALFA D 2564 B shows good machine runnability, and is medium fast setting.
The film of **ALFA D 2564 B** is transparent, the surface is light to strong sticky.

Specifications:

Content	softener free copolymer dispersion
Solid content	approx. 50%
Viscosity	pasty
pH Value:	approx. 6
Tear resistance:	approx. 0.15 N/mm ²
Medium size of particles	0.5 ... 2.0 my
Storage	tightly closed, possible for at least 6 months by temperatures +5°C...+40°C
Cleaning	washable with water
Dangerous contents	none

The adhesive is frost sensitive ! Temperatures below 0°C will destroy the glue.

Instructions:

ALFA D 2564 B is in accordance with food regulations BfR XIV.

Important notice:

The particulars on this data sheet are based on our present knowledge and experience. Of course each user has to make his own tests when using our products. Our data sheet cannot be considered legally binding in the case of certain material or suitability for all applications. Rules and legislations in each country have to be taken into consideration and we cannot be held responsible for local regulations unknown to us.

In case of any problem, please consult us.

February 2011